




600V PVC輕便電纜 (VCT)  
單芯



CNS 6556 , JIS C 3312

標稱截面積 mm <sup>2</sup>	導 體		絕緣厚度 mm	完成外徑 (約) mm	最大導體電阻 (20°C) Ω/km		最小絕緣電阻 (20°C) MΩ-km	參 考 值	
	構 成 單線數/單線徑 mm	外徑 (約) mm			軟 銅 線	鍍 錫 軟 銅 線		概 算 重 量 Kg/km	標 準 長 度 m
0.75	30/0.18	1.1	2.3	5.7	24.4	25.8	50	41	200
1.25	50/0.18	1.5	2.3	6.1	14.7	15.5	50	50	200
2.0	37/0.26	1.8	2.3	6.4	9.50	9.91	50	60	200
3.5	45/0.32	2.5	2.4	7.3	5.09	5.38	40	85	200
5.5	70/0.32	3.1	2.6	8.3	3.27	3.46	40	115	200
8	50/0.45	3.7	2.9	9.5	2.32	2.45	40	155	200
14	88/0.45	4.9	3.2	11.5	1.32	1.39	40	240	200
22	7/20/0.45	7.0	3.6	14.5	0.844	0.892	30	380	200
30	7/27/0.45	8.1	3.7	15.5	0.625	0.661	30	480	200
38	7/34/0.45	9.1	3.9	17.0	0.496	0.525	30	580	200
50	19/16/0.45	10.4	4.0	18.5	0.389	0.411	30	705	200
60	19/20/0.45	11.6	4.1	20	0.311	0.329	30	850	200
80	19/27/0.45	13.5	4.5	23	0.230	0.243	30	1140	200
100	19/34/0.45	15.2	4.6	25	0.183	0.193	20	1370	200

註：A.C.試驗電壓3KV，1分鐘。