



圓形 600V PVC 絕緣 PVC 被覆電纜 (VV)  
3芯

CNS 3301, JIS C 3342

導 體			絕緣體 厚 度 mm	被 覆 厚 度 mm	完 成 外 徑 (約) mm	導 體 電 阻 (20°C) Ω/km	試 驗 電 壓 (A.C.) V/1min	絕 緣 電 阻 (20°C) MΩ-km	參 考			
標 稱 截 面 積 mm <sup>2</sup> 或 直 徑 mm	構 成 (股數/ 單線徑) mm 或 形 狀	外 徑 mm							概 算 重 量 Kg/km	標 準 長 度 m	標 準 包 裝 法	
2.0	7/0.6	1.8	0.8	1.5	11.0	9.42	1500	50	165	200	捲 裝	
3.5	7/0.8	2.4			12.5	5.30			235			
5.5	7/1.0	3.0	1.0		14.5	3.40			335			
8	7/1.2	3.6	1.2	1.5	16.5	2.36	2000	40	465	300	軸 裝	
	圓形壓縮	3.4			16.0	2.34			435			
14	7/1.6	4.8	1.4		1.6	20			1.33			2500
	圓形壓縮	4.4		19.0		1.34	670					
22	7/2.0	6.0	1.6	1.7		24	0.840	3000	20			
	圓形壓縮	5.5			23	0.849	1000					
※30	7/2.3	6.9	1.8		1.8	25.2	0.635					3000
	圓形壓縮	6.4		24.1		0.622	1290					
38	7/2.6	7.8	1.8	1.9		29	0.497	3000	20			
	圓形壓縮	7.3			28	0.491	1630					
※50	19/1.8	9.0	1.8		2.0	31.0	0.386			3000	30	2090
	圓形壓縮	8.4		29.5		0.373	2010					
60	19/2.0	10.0	2.0	2.1		34	0.309	3000	20			2480
	圓形壓縮	9.3			33	0.311	2370					
※80	19/2.3	11.5	2.0		2.2	37.6	0.234			3000	30	3250
	圓形壓縮	10.7		35.9		0.234	3120					
100	19/2.6	13.0	2.2	2.3		42	0.184	3000	20			3990
	圓形壓縮	12.0			40	0.187	3780					
※125	19/2.9	14.5	2.2		2.4	45.5	0.147			3000	20	4910
	圓形壓縮	13.5		43.2		0.149	4720					
150	37/2.3	16.1	2.2	2.5		50	0.120	3000	30			5810
	圓形壓縮	14.7			47	0.124	5520					
200	37/2.6	18.2	2.4		2.8	56	0.0940			3000	20	7330
	圓形壓縮	17.0		53		0.0933	7260					
250	61/2.3	20.7	2.4	2.9		62	0.0736	3000	20			9300
	圓形壓縮	19.0			58	0.0754	8980					
325	61/2.6	23.4	2.6		3.1	69	0.0576			3000	20	11780
	圓形壓縮	21.7		65		0.0579	11530					
直徑 1.0	—	1.0	0.8	1.5		9.1	23.3	1500	50			100
1.2	—	1.2			9.5	16.1	120					
1.6	—	1.6			10.5	9.10	155			200		
2.0	—	2.0			11.5	5.76	200					
2.6	—	2.6			1.0	13.5	3.42			305	150	
3.2	—	3.2			1.2	16.0	2.25			435		300

註：附加※記號者為廠內設計。