



圓形 600V PVC 絕緣 PVC 被覆電纜 (VV)
4芯

CNS 3301, JIS C 3342

導 體			絕緣體 厚 度 mm	被 覆 厚 度 mm	完 成 外 徑 (約) mm	導 體 電 阻 (20°C) Ω/km	試 驗 電 壓 (A.C.) V/1min	絕 緣 電 阻 (20°C) MΩ·km	參 考		
標 稱 截面積mm ² 或 直 徑 mm	構 成 (股數/ 單線徑) mm 或 形 狀	外 徑 mm							概 算 重 量 Kg/km	標 準 長 度 m	標 準 包 裝 法
2.0	7/0.6	1.8	0.8	1.5	12.0	9.42	1500	50	200	200	捲 裝
3.5	7/0.8	2.4			13.5	5.30			290	150	
5.5	7/1.0	3.0	1.0	1.2	16.0	3.40	2000	40	420	300	軸 裝
8	7/1.2	3.6	18.0		2.36	590			550		
	圓形壓縮	3.4	17.5	2.34	550						
14	7/1.6	4.8	1.4	1.6	22	1.33	2500	30	945	200	軸 裝
	圓形壓縮	4.4		1.5	21	1.34			875		
22	7/2.0	6.0	1.6	1.7	27	0.840	3000	20	1390	150	軸 裝
	圓形壓縮	5.5			25	0.849			1290		
※30	7/2.3	6.9	1.8	1.8	28	0.635	1500	50	1720	300	軸 裝
	圓形壓縮	6.4		1.7	26.6	0.622			1650		
38	7/2.6	7.8	2.0	1.9	32	0.497	2000	40	2180	200	軸 裝
	圓形壓縮	7.3			31	0.491			2100		
※50	19/1.8	9.0	2.2	2.0	34.4	0.386	2500	30	2690	150	軸 裝
	圓形壓縮	8.4			33.0	0.373			2600		
60	19/2.0	10.0	2.4	2.1	38	0.309	3000	20	3210	200	軸 裝
	圓形壓縮	9.3			36	0.311			3090		
※80	19/2.3	11.5	2.6	2.3	42.0	0.234	1500	50	4200	300	軸 裝
	圓形壓縮	10.7			2.2	39.9			0.234		
100	19/2.6	13.0	2.8	2.5	47	0.184	2000	40	5200	200	軸 裝
	圓形壓縮	12.0			2.4	44			0.187		
※125	19/2.9	14.5	3.0	2.6	50.8	0.147	2500	30	6380	150	軸 裝
	圓形壓縮	13.5			2.5	48.2			0.149		
150	37/2.3	16.1	3.2	2.8	56	0.120	3000	20	7550	200	軸 裝
	圓形壓縮	14.7			2.7	52			0.124		
200	37/2.6	18.2	3.4	3.0	62	0.0940	1500	50	9590	300	軸 裝
	圓形壓縮	17.0			2.9	59			0.0933		
250	61/2.3	20.7	3.6	3.3	69	0.0736	2000	40	12200	200	軸 裝
	圓形壓縮	19.0			3.1	65			0.0754		
325	61/2.6	23.4	3.8	3.6	77	0.0576	2500	30	15240	150	軸 裝
	圓形壓縮	21.7			3.4	73			0.0579		
直徑1.0	—	1.0	0.8	1.5	9.8	23.3	1500	50	125	300	捲 裝
1.2	—	1.2			10.5	16.1			145		
1.6	—	1.6	1.0	1.5	11.5	9.10	2000	40	190	200	捲 裝
2.0	—	2.0			12.5	5.76			250		
2.6	—	2.6	1.2	1.5	15.0	3.42	2500	30	385	300	軸 裝
3.2	—	3.2			17.0	2.25			550		

註：附加※記號者為廠內設計。