



圓形 600V PVC 絕緣 PVC 被覆電纜 (VV)
2 芯

CNS 3301, JIS C 3342

導 體			絕緣體 厚 度 mm	被 覆 厚 度 mm	完 成 外 徑 (約) mm	導 體 電 阻 (20°C) Ω/km	試 驗 電 壓 (A.C.) V/1min	絕 緣 電 阻 (20°C) MΩ-km	參 考		
標 稱 截面積 mm ² 或 直 徑 mm	構 成 (股數/ 單線徑) mm 或 形 狀	外 徑 mm							概 算 重 量 Kg/km	標 準 長 度 m	標 準 包 裝 法
2.0	7/0.6	1.8	0.8	1.5	10.5	9.42	1500	50	135	300	捲 裝
3.5	7/0.8	2.4			11.5	5.30			180	200	
5.5	7/1.0	3.0	1.0		13.5	3.40			260	150	
8	7/1.2	3.6	1.2		15.5	2.36			360		
	圓形壓縮	3.4			15.5	2.34			330		
14	7/1.6	4.8	1.4		19.0	1.33			555	40	
	圓形壓縮	4.4		18.0	1.34	505					
22	7/2.0	6.0	1.6	1.6	23	0.840	815				
	圓形壓縮	5.5		1.5	21	0.849	730				
※30	7/2.3	6.9	1.6	1.6	23.4	0.635	935				
	圓形壓縮	6.4			22.4	0.622	925				
38	7/2.6	7.8	1.7	1.7	27	0.497	1250				
	圓形壓縮	7.3			26	0.491	1170				
※50	19/1.8	9.0	1.8	1.8	28.8	0.386	1520				
	圓形壓縮	8.4			27.6	0.373	1440				
60	19/2.0	10.0	1.9	1.9	32	0.309	1820				
	圓形壓縮	9.3			31	0.311	1700				
※80	19/2.3	11.5	2.0	2.0	35.0	0.234	2360				
	圓形壓縮	10.7			33.4	0.234	2240				
100	19/2.6	13.0	2.2	2.2	39	0.184	2900				
	圓形壓縮	12.0			2.1	37	0.187	2680			
※125	19/2.9	14.5	2.2	2.3	42.4	0.147	3500				
	圓形壓縮	13.5			2.2	40.2	0.149	3340			
150	37/2.3	16.1	2.5	2.5	47	0.120	4100				
	圓形壓縮	14.7			2.3	44	0.124	3870			
200	37/2.6	18.2	2.4	2.7	52	0.0940	5170				
	圓形壓縮	17.0			2.6	50	0.0933	5090			
250	61/2.3	20.7	2.9	2.9	58	0.0736	6530				
	圓形壓縮	19.0			2.7	54	0.0754	6210			
325	61/2.6	23.4	2.6	3.1	64	0.0576	8230				
	圓形壓縮	21.7			3.0	61	0.0579	8000			
直徑1.0	—	1.0	0.8	1.5	8.7	23.3	1500	50	85	捲 裝	
1.2	—	1.2			9.1	16.1			95		
1.6	—	1.6			9.9	9.10			130		
2.0	—	2.0			11.0	5.76			160		
2.6	—	2.6			13.0	3.42			240		
3.2	—	3.2			15.0	2.25			335		

註：附加※記號者為廠內設計。